



Technical sheet

POLYWEAVE™

End use	A horticultural grade plastic film with a variety of applications including greenhouse roll up sides or ends, covering of doors, animal shelters, gazebos etc.			
Product Description	A three layer translucent fabric consisting of two outer clear layers of polythene on each face of a central woven scrim.			
Warranty	30 month pro-rata U.V. warranty, conditions apply			
Sizes	Roll Width 2.7m 4m	Length Cut to length	Weight 0.164kg/sqm 0.164kg/sqm	Code POLW2.7 POLW4
Thickness	300 microns +/- 10% Manufacturing Tolerance			
Structural Properties	A woven polyethylene fabric that is laminated to a clear U.V. stabilized film, providing a translucent yet flexible material that offers extreme wear and tear resistance.			
Other Accessories	Lockstrip or Duralock film fastening systems may be used to secure Polyweave to framework.			

APPLICATION / INSTALLATION:

For a complete installation guideline please refer to the redpath film installation guidelines - these can be viewed on www.redpath.co.nz web site under the heading greenhouse films. Polyweave is commonly used for sidewall rolling walls, lean-to applications or as a high strength roof covering. Polyweave can be installed with either side facing to the outside. Polyweave should be secured to the structure with a reliable greenhouse film holding system (e.g Duralock 2). Pull the polyweave as tight as possible & avoid leaving wrinkles or folds in the film.

SAFETY DATA:

Wash hands after handling polyethylene products , especially before preparing food
Keep material away from open flame
Dispose of waste / used polythene materials with appropriate care

